



**NIMS, HOWES, COLLISON, HANSEN & LACKERT  
PATENT, TRADEMARK AND COPYRIGHT MATTERS**

605 Third Avenue  
New York, NY 10058  
Phone: (212) 661-9700  
Fax: (212) 661-9213



EXPRESS MAIL No.: EJ371193109US

Deposited: **August 4, 1999**

I hereby certify that this correspondence is being deposited with the United States Postal Service Express mail under 37 CFR 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, DC 20231

*Beatrice Cahn*

/ **Beatrice Cahn**

Assistant Commissioner for Patents  
Washington, DC 20231

Date: **August 4, 1999**  
Docket No: 11598/9-1276

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**UTILITY PATENT APPLICATION TRANSMITTAL**

(Only for new nonprovisional applications under CFR 1.53(b))

Docket No.:	11598/9-1276
Inventor(s):	Tiang Fong HAN
Title:	STUD AND RIDER FOR USE ON MATRIX TRAYS

**APPLICATION ELEMENTS** (See MPEP chapter 600 concerning utility patent application contents)

- ☒ 1. Fee Transmittal Form (attachment)
- ☒ 2. Specification, Claims, Abstract [Total pages 10]
- ☐ 3. Formal Drawing(s) (35 USC 113) [Total sheets ]
- ☒ Informal Drawing(s) (35 USC 113) [Total sheets 11]
- ☒ 4. Oath or Declaration [Total pages 1 ]
- ☐ Unexecuted Declaration [Total pages ]
- ☒ a. Newly executed (original or copy)
- ☐ b. Copy from a prior application (37 CFR 1.63(d))  
(For continuation/divisional with box 17 completed)
- ☐ i. **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named  
in the Prior application see 37 CFR 1.63(d)(2) & 1.33(b).

- ☐ 5. Incorporation by Reference (useable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
- ☐ 6. Microfiche Computer Program (Appendix)
- ☐ 7. Nucleotide and/or Amino Acid Sequence Submission (If applicable, all necessary)
- ☐ a. Computer Readable Copy
  - ☐ b. Paper Copy (identical to computer copy)
  - ☐ c. Statement verifying identity of above copies

#### ACCOMPANYING APPLICATION PARTS

- ☐ 8. Assignment Papers (cover sheet (PTO-1595) and document(s))
- ☐ 9. 37 CFR 3.73(b) Statement (when there is a assignee) ☐ Power of Attorney
- ☐ 10. English Translation Document (if applicable)
- ☐ 11. Information Disclosure Statement (IDS) and PTO-1449 ☐ Copies of IDS citations (refs. )
- ☒ 12. Preliminary Amendment
- ☒ 13. Return Receipt Postcard (MPEP 503) (should be specifically itemized)
- ☒ 14. Small Entity Statement ☐ Statement filed in prior application, Status still proper and desired
- ☐ 15. Certified Copy of Priority Document(s): filed
- ☒ (if foreign priority is claimed) - Singapore Patent Application No. 9902708-8 filed 7 June 1999.
- ☐ 16. Other:
- ☐ 17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment:
- ☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP)
- of prior application No. \_\_\_\_\_

Prior application information: Examiner \_\_\_\_\_ Group: \_\_\_\_\_

☒ 18. **CORRESPONDENCE ADDRESS**

Please direct all communications to William J. Sapone, Esq. at  
the offices of Nims, Howes, Collison, Hansen & Lackert  
605 Third Avenue, New York, NY 10058 (212) 661-9700.

Respectfully requested.

Nims, Howes, Collison, Hansen & Lackert

August 4, 1999  
605 Third Avenue  
New York, NY 10058  
Tel. (212) 661-9700  
(Appl99)

By:   
William J. Sapone - Reg. No. 32,518  
Attorney for Applicant(s)

## Fee Transmittal Form

Docket No.:	11598/9-1276
Inventor(s):	Tiang Fong HAN
Title:	STUD AND RIDER FOR USE ON MATRIX TRAYS

---

**THE FILING FEE HAS BEEN CALCULATED AS SHOWN BELOW:**

	Claims filed		Extra	SMALL \$ 380.00	LARGE \$ 760.00	AMOUNT \$380.00
Total Claims	12	Minus 20	0	x \$ 09.00	x \$ 18.00	\$
Independent	1	Minus 03	0	x \$ 39.00	x \$ 78.00	\$ .00
Multiple dependent claim fee				+ \$ 130.00	+ \$ 260.00	\$ .00
( ) Non-English specification 37 C.F.R. 1.17(k) fee (+ \$130.00)						\$ .00
Assignment Papers (cover sheet (PTO-1598) and documents						\$ .00
<b>FEE ENCLOSED:</b>						<b>\$380.00</b>

[ X ] A check in the amount of **\$380.00** is enclosed.  
 The Commissioner is hereby authorized to charge any additional fees required with this submission or to credit any overpayment to Deposit Account No. 14-1115.

- a. ☒ Fees required under 37 C.F.R. 1.16.
- b. ☒ Fees required under 37 C.F.R. 1.17.
- c. ☐ Fees required under 37 C.F.R. 118.

Respectfully submitted,

Nims, Howes, Collison, Hansen & Lackert

August 4, 1999  
 605 Third Avenue  
 New York, NY 10058  
 Tel. (212) 661-9700  
 WJS/bc  
 (appl99)

By:   
 William J. Sapone - Reg. No. 32,518

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Applicant or Patentee: Tiang Fong HAN

Docket No.: 11589/9-1276

Serial or Patent No: To be Assigned

Filed: Herewith -

For: STUD AND RIDER FOR USE ON MATRIX TRAYS

**VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS**  
**(37 C.F.R. 1.9(f) and 1.27(b)) - INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 C.F.R. 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled STUD AND RIDER FOR USE ON MATRIX TRAYS  
described in:

- ☒ the specification filed herewith
- ☐ Provisional application serial no. \_\_\_\_\_ filed \_\_\_\_\_.
- ☐ patent no. \_\_\_\_\_, issued \_\_\_\_\_.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 C.F.R. 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 C.F.R. 1.9(d) or a nonprofit organization under 37 C.F.R. 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey or license any rights in the invention is listed below:

- ☐ no such person, concern or organization
- ☐ persons, concerns or organizations listed below\*

**\*NOTE:** Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 C.F.R. § 1.27).

NAME:

ADDRESS:

☒ INDIVIDUAL      ☐ SMALL BUSINESS CONCERN      ☐ NONPROFIT ORGANIZATION

NAME:

ADDRESS:

☐ INDIVIDUAL      ☐ SMALL BUSINESS CONCERN      ☐ NONPROFIT ORGANIZATION



EXPRESS MAIL CERTIFICATE

Date August 4, 1999 Label No. EL 371193109US

I hereby certify that, on the date indicated above I deposited this paper or fee with the U.S. Postal Service & that it was addressed for delivery to the Assistant Commissioner for Patents, Washington, DC 20231 by "Express Mail Post Office to Addressee" service.

Beatrice Cahn

Name (Print)

Beatrice Cahn

Signature

File No. 11598/9-1276

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Tiang Fong HAN

Serial No.: To be Assigned

Group Art Unit:

Filed : Herewith - August 4, 1999

Examiner:

For : STUD AND RIDER FOR USE ON MATRIX TRAYS  
-----

Assistant Commissioner for Patents  
Washington, DC 20231

**PRELIMINARY AMENDMENT**

Sir:

Prior to the examination of the above-referenced application, please amend the above-identified application as follows:

**IN THE CLAIMS**

In claim 3, line 1, delete "any one of the preceding claims or", insert --claim 1--.

In claim 4, line 1, delete "any one of the preceding claims or", insert --claim 1--.

In claim 6, line 1, delete "any one claims 4 or 5", insert --claim 4--.

In claim 7, line 1, delete "any one claims 4 to 6", insert --claim 4--.

In claim 8, line 1, delete "any one claims 4 to 6", insert --claim 4--.

In claim 9, line 1, delete "any one of the preceding claims", insert --claim 1--.

In line 2, after "recess", insert --for--; before "the", delete "for".

In claim 10, line 1, delete "any one of the preceding claims", insert --claim 1--.

Claim 11. (Amended) The carrier of [any one of the preceding claims being] claim 1 wherein the carrier is a semiconductor chip matrix tray.


In claim 12, line 1, delete "any one of the preceding claims" insert --claim 1--.

Cancel claim 13.

### Remarks

Entry of this agreement is respectfully requested to eliminate multiple claim dependencies to reduce the filing fee and to clarify the claim language.

Respectfully submitted,

  
William J. Sapone  
Registration No. 32,518  
Attorney for Applicant(s)

**NIMS, HOWES, COLLISON,  
HANSEN & LACKERT**  
605 Third Avenue  
New York, NY 10158-9213  
Phone: (212) 661-9700  
Fax: (212) 661-9213  
WJS/bc  
(#appl99)



## **STUD AND RIDER FOR USE ON MATRIX TRAYS**

### **Technical Field**

This invention relates to carriers for objects and more particularly to the easy identification and/or orientation of such carriers during manufacturing processes.

- 5 The invention has particular relevance to the semiconductor industry.

### **Background Art**

In the semiconductor industry semiconductor chips such as microprocessors and the like are packaged on carriers called matrix trays. The matrix trays carry a number of semiconductor chips which are passed along a production line for  
10 assembly of completed circuit boards. The matrix trays are typically injection moulded plastics having a height of about 1cm.

The trays carry technical information relevant to the tray, the chips carried or the process, such as temperature rating, part number, date code, etc. This technical information is usually embossed on the edge of the tray, which is typically about  
15 1cm high. As the trays flow through the production line the following inconveniences occur:

1. Difficulty in reading the embossed descriptions on tray surfaces, especially when they are stacked high. The printed information is not large enough due to the limited space on the edge of the tray. Also, the printed  
20 characters and numbers are the same colour as the tray's surfaces so there is little contrast to aid in reading them.

2. Difficulty in identifying trays that house good chips as against those used to store rejected ones. When bad chips are identified and segregated by the machines during the assembly process, they are separated but housed onto the

same type of trays. The same type of trays are needed as they are specifically designed to house a particular size and family type of chips.

3. Difficulty in identifying different types of chips within a family that use the same body dimension of the tray. As different machines are required for handling a particular type of chip within a family, the use of the common tray makes it difficult to identify the correct chips for each machine.

4. Difficulty in identifying the correct tray orientation during the machine loading. The tray must be loaded manually with a specific orientation. Although present trays come with a tiny corner chamfer on one of its corners, it is not conspicuous enough to ensure correct loading onto the machine.

It has been proposed to use coloured stickers to help differentiate certain trays from others. However, the stickers need to be removed before delivery to customers and this sometimes leaves adhesive material on the tray.

#### **Disclosure of the Invention**

15 In an attempt to overcome at least some of the disadvantages of existing matrix trays, in one broad form the invention provides a carrier for supporting one or more articles, the carrier including:

a main body having at least one engagement means; and

20 at least one indicator means for engagement with the engagement means, the or each at least one indicator means including means to provide information visually or tactually to an observer regarding the carrier or the articles supported thereon or both.

In a preferred form, the invention is a semi conductor matrix tray having at least one removable indicator means. The indicator means may be positioned prominently along one side of the tray and be assigned different colours, shapes or numbers to indicate technical information. Preferably the colours used for the

indicator means contrast with the colour of the tray adjacent the indicator means.

Preferably the indicator means slides into a receptacle on one side of the tray. Preferably the receptacle and the indicator means are shaped so that only one  
 5 orientation of the indicator means relative to the receptacle is allowed. The indicator means may have a receptacle which receives a protrusion on the tray.

Preferably the indicator means includes a first part which engages in or on the edge of the tray and a second part mounted on the first part. The first part may then be made of one of a series of different colours whilst the second part may  
 10 also be made of one of a series of different colours and/or shape.

One or both of the first and second parts may be of a contrasting colour to the tray or the same colour. The second part may partially or totally obscure the first part when the indicator is mounted on the tray.

More than one indicator may be used on the one tray.

15 The invention will be more easily understood from the following non limiting description of a preferred embodiment and the drawings in which:

#### **Brief Description of the Drawings**

Figure 1 is a plan view of a matrix tray made according to the present invention.

Figure 2 is a front side view of the matrix tray of Figure 1.

20 Figure 3 is a rear side view of the matrix tray of Figure 1.

Figure 4 is a plan view of the end area of the tray of Figure 1 indicated by arrow K.

Figure 5 is an end elevation of the area indicated by the arrow K.

Figure 6 is a front elevation view of a rider portion of an indicator for use with the tray of Figure 1.

Figure 7 is a rear elevation view of the rider of Figure 6.

Figure 8 is a cross-sectional view taken along line AA in Figure 6.

5 Figure 9 is an end elevation of the Figure 6 rider.

Figure 10 is a rear elevation view of a stud for use with the rider of Figures 6 to 9.

Figure 11 is an end elevation view of the stud of Figure 10.

Figure 12 is a cross-sectional view of the stud taken along line BB in Figure 10.

#### 10 **Best Mode of Carrying out the Invention**

Referring to Figures 1 to 5 there is shown a matrix tray 10 configured to carry semiconductor chips in a 5 x 2 array. Each chip is carried in a receptacle 12. The tray 10 carries on its front side 14 temperature rating information 16 and a part number 18. Its rear side 20 also carries a part number 22 and other  
15 information 24. This information is moulded into the plastics of the tray in manufacture and so is inherently difficult to read. In the prior art this is all that is available for operators to identify the trays, their content and other information relevant to the manufacturing process.

In the tray of Figures 1 to 5 one end 26 is provided with a slot 28 in its end wall  
20 30 (see Figures 4 and 5). This slot is generally rectangular in shape having vertical sides 32 and horizontal base 34. The sides 32 are angled at about 60° to the end wall 30 so the width of the front of the slot 28 is less than the width at its rear. The base 34 has a semicircular protrusion 36 extending upwards. The protrusion is located off centre of the slot 28.

Referring to Figures 6 to 9 there is shown a rider 40 for insertion into the slot 28 of the tray 10. The rider 40 is generally rectangular and has the same overall width, depth and height as the slot 28. The ends 42 of the rider are also angled at 60° so that the rider may be slid into the slot 28. It will be appreciated that the angling of the ends of the slot 28 and rider 40 mean that the rider is trapped in the slot 28 and cannot fall out of the front of the recess. The bottom of the ends is chamfered at 46 to aid insertion of the rider into slot 28. The base of the rear face is also preferably chamfered at 49 to aid insertion.

The bottom edge 44 of the rider has a semicircular recess 48 which corresponds to the protrusion 36 in the slot 28. The protrusion 36 and recess 48 prevent the rider being fully inserted into the slot 28 upside down.

Protruding from the front face 50 of the rider are three identical circular protrusions 52a, b and c. These protrusions 52 are preferably equally spaced from each other with the middle protrusion 52b located at the horizontal centre of the rider. Preferably the protrusions 52 extend horizontally along a line slightly below the vertical centre of the rider. The thickness of the main portion of the rider is equal to that of the slot 28, so the protrusions 52 extend proud of the end wall 30.

Referring to Figures 10 to 12 there is shown a stud 60 for use with the rider 40. The stud 60 is generally rectangular with a planar front surface 62. The rear surface 64 has a rectangular recess 66 therein defined by peripheral walls 68 and side walls 74. Located in the centre of this recess 66 and extending from the base surface 70 toward the rear surface 64 is a circular pin 72. Preferably this pin extends just short of the rear surface 66.

The width between the side peripheral walls 74 and the distance between the pin 72 and the end walls is very slightly less than the diameter of the pins 52 of the rider 40 so that the stud may be mounted on the rider 40 by pressing the stud onto two of the pins 52 in an interference fit. This interference fit is preferably loose enough to enable easy separation and assembly of the two

parts but tight enough to prevent accidental separation. The rider may be placed on the centre pin 52b and left hand pin 52a or the centre pin 52b and right hand pin 52c. Whilst a "two pin" stud has been shown, it will be appreciated that a "three pin" stud which obscures all of the rider 40 may be used.

- 5 Because the rider has the same depth as the slot 28, the stud sits proud of the end wall. Further, because the protrusions 52 sit slightly below the centre-line of the rider, the bottom of the stud overlaps the end wall 30. The stud also overlaps the edge of the end wall, due to the angling of the ends of the slot 28. This overlapping of the end wall is neither essential or disadvantageous. If  
10 desired, the rider and stud may be made so that the stud overlaps the end wall 30 to a greater extent or not at all.

- The tray 10, rider 40 and stud 60 can be manufactured either of low or high temperature material, which is able to withstand baking temperatures from 0 degrees to 200 degrees Celsius. For low temperature materials ABS plastics  
15 can be used. For high temperature materials, preferably compounded fiber plastics are used. Preferably the parts are manufactured in different colours to provide immediate visual information to the user. Preferably, the same material is used for all components to avoid problems with different rates of thermal expansion, but this is not essential. As examples, the tray may be manufactured  
20 of a blue plastics material with the rider being manufactured in red, yellow and orange colours. The stud may be manufactured in white and blue colours. This gives six different rider/stud colour combinations.

- The colour of the rider may be used to indicate a temperature rating whilst the colour of the stud could be used to indicate the status of the chips to be housed.  
25 One colour could mean good chips and another colour could mean reject chips requiring further analysis.

A second rider/stud may be provided to indicate the specific chip in a family of chips which is carried by the tray. Additional recesses and indicators as needed fall within the scope of the invention.

The use of contrasting colours also aids the user in both segregating different "types" of trays from each other but also aids in correct alignment. For example, a yellow rider with a red 2 pin stud may be provided. The user will be educated to align the trays with the rider/stud combination at one end with the exposed  
5 part of the yellow rider to the right of the red stud.

It will be appreciated that the rider may be provided with more than three pins. For example, a four pin rider will allow a "two pin" stud to be placed centrally, with a pin exposed on either side or to be located to one side, with two pins exposed on either the left or right. Use of a three pin stud would allow one or two  
10 pins to be exposed, to either the left or right side of the stud. Thus the number and position of the exposed pins may be used in sorting and alignment, as well as the colours of the pin and stud.

Whilst the engagement of the rider with the tray in the preferred form of the invention utilises a recess into which the rider slides, the invention is not limited  
15 to this specific format. For example, the same pin/recess interference fit type engagement may be utilised to attach the rider to the tray.

It will be appreciated that many modifications may be made to the embodiment described herein to those skilled in the art without departing from the spirit or scope of the invention.

### The Claims

1. A carrier for supporting one or more articles, the carrier including:  
  
a main body having at least one engagement means; and  
  
5 at least one indicator means for engagement with the engagement means, the or each at least one indicator means including means to provide information visually or tactually to an observer regarding the carrier or the articles supported thereon or both.
2. The carrier of claim 1 wherein said visual or tactile information is  
10 provided by different colour or colours of the indicator means or by different shaped portions of the indicator means or both.
3. The carrier of any one of the preceding claims or wherein at least part of the or each indicator means is a different colour to the main body adjacent the indicator means.
- 15 4. The carrier of any one of the preceding claims wherein the or each one indicator means includes a first part adapted to engage the main body and a second part attached to the first part.
5. The carrier of claim 4 wherein the second part is releasably attached to the first part.
- 20 6. The carrier of any one of claims 4 or 5 wherein the second part is attachable to the first part in at least two positions or at least two orientations or both.
7. The carrier of any one of claims 4 to 6 wherein the first part or the  
25 second part or both include portions whose shape provides visual information to the user.



8. The carrier of any one of claims 4 to 6 wherein one of the first and second part has at least one protrusion and the other has at least one recess for receiving the at least one protrusion.

9. The carrier of any one of the preceding claims wherein the  
5 engagement means or each indicator means includes a recess receiving for the other.

10. The carrier of any one of the preceding claims wherein the engagement means and indicator means are configured such that the indicator means only correctly engages in the respective engagement means in one  
10 orientation.

11. The carrier of any one of the preceding claims being a semiconductor chip matrix tray.

12. The carrier of any one of the preceding claims wherein one or both of the body and the at least one indicator means is made of a material capable  
15 of withstanding a baking temperature range of 0 to 200 degrees Celsius.

13. A carrier, substantially as herein described with reference to the drawings.

**ABSTRACT****STUD AND RIDER FOR USE ON MATRIX TRAYS**

A carrier for articles has a main body (10) with one or more engagement means (28) for receiving one or more indicators (40, 60). The indicators (40, 60) have  
5 one or more contrasting colours compared to the colour of the main body (10).  
The colour or shape or both of the indicator provides the user with information regarding the articles, carrier or characteristics of the articles or carrier.

(Fig. 1)





Figure 1

Figure 2






Figure 3




Figure 4




Figure 5




Figure 6






Figure 7




Figure 8




Figure 9




Figure 11




Figure 10




Figure 11

## DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that.

My residence, post office address and citizenship are the same as stated below next to my name

I believe I am an original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) the subject matter which is claimed and for which a patent is sought on the invention entitled: STUD AND RIDER FOR USE ON MATRIX TRAYS, the specification of which

(check one)



is attached hereto.



was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_

and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed

Prior Foreign Application:

Priority Claimed:

<u>9902708-8</u> (Number)	<u>SINGAPORE</u> Country	<u>7 June 1999</u> (Day/Month/Year)	Yes <u>X</u> No ____
_____ (Number)	_____ Country	_____ (Day/Month/Year)	Yes ____ No ____
_____ (Number)	_____ Country	_____ (Day/Month/Year)	Yes ____ No ____

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulation, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status -patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status -patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: The undersigned hereby appoints as its attorney: William J. Sapone, Registration No. 32,518 and Robert L. Powley, Registration No. 42,087 all of Nims, Howes, Collison, Hansen & Lackert, 605 Third Avenue, New York, New York 10158, U.S.A.

Address all telephone calls to William J. Sapone, Esq. at Telephone No. (212) 661-9700  
Address all correspondence to William J. Sapone, Esq.  
NIMS, HOWES, COLLISON,  
HANSEN & LACKERT  
605 THIRD AVENUE  
New York, N.Y. 10158, U.S.A.

I hereby declare that all statements made herein of my own knowledge are true, and that all statements made on information and belief are believed to be true, and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon

(Full name of first inventor: Tiang Feng HAN)

Inventor's signature X. [Signature] Date: July 21, 1999

Residence: 16 Jalan Teliti, Singapore 537308 Citizenship: Singapore 537308

Post Office Address: 16 Jalan Teliti, Singapore 537308

6/20/99 11:59 AM